

# EZ VENT® / EZ PURGE® / EZ VENT-PURGE®

## SLIP BLINDS | AVAILABLE FOR RENT OR SALE

USA Industries' EZ Series slip blinds are safer alternatives to the traditional paddle blind — each engineered for a specific isolation, venting, or purging task in refinery, chemical, and power-generation service.



### EZ VENT

**Block flow on one side. Vent through the other.**

A safer, smarter alternative to the traditional paddle blind. The ported side lets crews verify zero energy in the line, relieve pressure that has bypassed an upstream valve, and provide a clean access point for hydrotesting.

#### KEY FEATURES

- Multiple ports at any position — vent one or both sides
- NPT or socket-weld port connections
- “V”-cut handle clearly identifies a vent blind
- Available in Ring Type Joint (RTJ)
- Rated or isolation thicknesses available

#### RECOMMENDED MIN. THICKNESSES

SW / NPT NPS (in.)	MIN. THK. SW (in.)	MIN. THK. NPT (in.)
1/8	3/4	1/2
1/4	7/8	3/4
3/8	1	7/8
1/2	1-1/4	1
3/4	1-1/2	1-1/4
1	1-3/4	1-1/2
1-1/4	2-3/16	1-3/4
1-1/2	2-7/16	2
2	3	2-1/2

- *Rated blinds may require increased thickness*
- *Machined finish may require increased thickness*



### EZ PURGE

**Built-in stand-off — no makeshift spacers.**

Eliminates the safety risk and gasket-surface damage caused by stacking a slip blind with spacers. The integrated stand-off delivers an even seal while creating a controlled gap for safe, effective line purging.

#### KEY FEATURES

- Fits any flange size and rating
- “P”-cut handle clearly identifies a purge blind
- Stamped with size and pressure rating
- Available in Ring Type Joint (RTJ)
- Typically 1/2” thick with 1/4”-deep purge area
- Blank side can be rated upon request



### EZ VENT-PURGE

**Two functions, one blind. Purge and vent simultaneously.**

Combines the strengths of the EZ Vent and EZ Purge into a single integrated solution, enabling safe line purging during hot work while controlling hazardous pressure or fluid on the upstream side.

#### KEY FEATURES

- Fits any flange size and rating, including RTJ
- Dual handle: “V” (vent) one side, “P” (purge) the other
- Flat black finish with color-coded handle
- Stamped with size and pressure rating
- Rated or isolation thicknesses available

**AVAILABLE**

**FOR RENT OR PURCHASE**

#### WHEN ORDERING — SPECIFY

- Line size
- Flange rating
- Thickness (isolation, pressure rated, custom)
- Material
- NPT or SW port type
- No. of ports (EZ Vent / Vent-Purge)
- Port location(s)
- Mill or serrated face
- Quantity
- Required delivery date



To learn more: **(800) 456-8721 • info@USAIndustries.com • USAIndustries.com**

M-PIP EZVT-EZPRG-EZVTPRG-2.0.1

S. Houston, TX | Corpus Christi, TX | Prairieville, LA | Broken Arrow, OK

©2026 USA Industries • ISO 9001:2015