



Fully Loaded EZ Lock Blind Rack® Options

OPTION 1: NON-RATED 5/16" CARBON STEEL ISOLATION THICKNESS BLINDS

SPECIAL PRICING!



LINE SIZE (IN)	FLANGE RATING					
	150#			300#		
	THKNS (IN)	QTY	WT/BLIND (LBS)	THKNS	QTY	WT/BLIND (LBS)
1/2	5/16	34	0.25	5/16	34	0.30
3/4	5/16	34	0.35	5/16	34	0.37
1	5/16	34	0.45	5/16	34	0.55
1-1/2	5/16	34	0.75	5/16	34	0.95
2	5/16	34	1.15	5/16	34	1.30
2-1/2	5/16	34	1.60	5/16	34	1.75
3	5/16	34	2	5/16	34	2.30
4	5/16	34	3.20	5/16	34	3.45
6	5/16	34	5.20	5/16	34	6.65
8	5/16	34	8.25	5/16	34	10.05
10	5/16	34	12.25	5/16	34	14
12	5/16	34	17.85	5/16	34	19
14	5/16	34	21.70	5/16	34	25
TOTAL 150# PIECES		442		TOTAL 300# PIECES		442

Standard isolation thickness is 5/16" (+/- 1-1/16").

Other sizes, thicknesses and alloys available.

Estimated Weight of Blind Rack:

Fully Loaded - 7,000LBS
Empty - 1,150LBS

OPTION 2: API 590 RATED CARBON STEEL HYDROTEST THICKNESS BLINDS

SPECIAL PRICING!



LINE SIZE (IN)	FLANGE RATING					
	150#			300#		
	THKNS (IN)	QTY	WT/BLIND (LBS)	THKNS	QTY	WT/BLIND (LBS)
1/2	5/16	34	1	5/16	34	1
3/4	5/16	34	1	5/16	68	1
1	5/16	32	2	5/16	64	2
1-1/2	5/16	30	2	5/16	30	2
2	5/16	30	2	3/8	50	3
2-1/2	5/16	28	2	3/8	25	4
3	5/16	28	2	3/8	44	5
4	3/8	28	6	1/2	20	9
6	1/2	22	12	5/8	16	18
8	1/2	20	17	7/8	24	34
10	5/8	16	28	1	10	51
12	3/4	14	47	-	N/A	N/A
14	3/4	14	59	-	N/A	N/A
TOTAL 150# PIECES		332		TOTAL 300# PIECES		385

Sizes and thicknesses meet ASME 16.48, API 590, ASME 16.5 specs.

Other sizes and alloys available.

Estimated Weight of Blind Rack:

Fully Loaded - 6,800LBS
Empty - 1,150LBS