



# LOW PRESSURE INFLATABLE PIPE PLUG

Natural Rubber Type-C Inflatable Pipe Plugs



**WARNING:** Never stand in front of an installed plug under pressure. Plugs ejected under pressure can cause serious bodily injury.

USA Industries' Inflatable Pipe Plug, also known as a pipe balloon plug, or pressure test balloon, expands to temporarily isolate pipes during repairs, or in the event of a spill. We offer them in line sizes from 1-1/2" through 72".

The innovative design allows the isolation plug to be smaller and more flexible which means it can be snaked through hot tap or branch pipes into larger pipelines that are otherwise inaccessible. Inflatable pipe plugs can inflate up to 8 times it's compact size to prevent the flow of liquids during maintenance work or to block pipes or drains in the event of a spill (connects with your air compressor). The compact size also means that this plug takes up minimal storage.

## PRODUCT FEATURES:

- Canvas outer shell with rubber bladder inside
- Heat resistant materials are safe for use up to 140° F
- Includes pressure gauge and 2' hose. Longer hoses are available upon request
- Expandable design conforms to a wide range of pipe diameters (I.D.); inflate partially or fully according to your application needs
- Ideally suited for short-term use
- When renting or purchasing, as an example, an 8" plug should be used on an 8" pipe

**NOTE: We do not recommend these be used for holding back-pressure\***

\*If holding backpressure is a requirement, ask us about our new and exclusive GripSafe® plugs, or one of our other low to high pressure rated high quality plugs

PART NO.	PLUG SIZE (in.)	INFLATION PRESSURE (psig)	BACK PRESSURE HOLDING CAPABILITY (up to)	TAP HOLE (in.)	WEIGHT (lbs.)
IP-BP-2	2	15	60% of Inflation Pressure	1	1/2
IP-BP-3	3			1	1/2
IP-BP-4	4			1-1/4	1
IP-BP-6	6			1-1/2	1
IP-BP-8	8	12		2	1-1/2
IP-BP-10	10	10		2	2
IP-BP-12	12	8		2-1/2	3
IP-BP-14	14	6		2-1/2	4
IP-BP-16	16			3	5
IP-BP-18	18			3	6
IP-BP-20	20			4	7
IP-BP-22	22	4		4	8
IP-BP-24	24	3.5		4	10
IP-BP-26	26	3		4	12
IP-BP-28	28			5	14
IP-BP-30	30			5	16
IP-BP-32	32			5	18
IP-BP-36	36	1		5	26
IP-BP-40	40			6	35
IP-BP-42	42			6	38
IP-BP-44	44			6	41
IP-BP-46	46			6	44
IP-BP-48	48			6	47
IP-BP-54	54			n/a	n/a
IP-BP-60	60		n/a	n/a	
IP-BP-66	66	n/a	n/a		
IP-BP-72	72	n/a	n/a		

**DO NOT** use bags in gasoline, kerosene, oil, acid or any similar substances unless special bags are made for this purpose.

**DO NOT** allow sparks, hot metal or welding slag to come into contact with bags.

**DO NOT** expose bags to temperatures in excess of 150° F or lower than -20° F.

**DO NOT** leave bags in direct sunlight for extended periods.

For more information on USA Industries products, contact us at (713) 941-3797 or go to [www.USAIindustries.com](http://www.USAIindustries.com)