

ENVIRONMENTALLY SUPERIOR

SURESNATM PRO

SNAP IT[®] TUBE PLUG HYDRAULIC INSTALLATION TOOL

Built to install Snap It[®] JR & SR Engineered Tube Plugs in heat exchangers, boilers, and condensers. No shop air, pumps, hoses, or electrical connections required, delivering a cleaner, safer worksite. The self-contained, hydraulic power is the environmentally superior alternative to traditional electric or pneumatic driven hydraulic power units.

CORDLESS • HOSELESS • BATTERY-OPERATED



OP. FORCE

11.2

tons

BATTERY TYPE

LXT 18v

5.0Ah lithium-ion

CHARGE TIME

≤ 40

minutes

PLUGS/CHARGE

400

(up to)

TOOL WEIGHT

5 lbs

2.3 kg

OP. TEMP

5-122°

-15°C TO 50°C

FEATURES

- Fully self-contained system, no plant air or electrical hookup required
- Adjustable Pull Head angle for installation in tight spaces where a straight-on approach isn't possible
- Integrated pressure sensor and automatic limit stop to prevent tool damage
- Compact design: 5 lbs. (2.3 kg) with heavy-duty grip
- Shoulder strap included



BENEFITS

- Eliminates hoses and trip hazards for safer, cleaner job sites
- Ergonomic, single-handed operation in confined spaces, remote areas, and elevated work zones
- Extended runtime with enhanced battery capacity
- Reduced operator fatigue via shoulder strap and ergonomic design
- No hydraulic fluids or external power; the environmentally superior alternative
- Long-lasting performance, engineered from premium 7075-T6 aluminum alloy, the same material used in aerospace structural components, the SureSnap PRO press foot withstands repeated high-pressure cycles

WARNING:

Never stand in front of or in line with any installed plug or tool under pressure. Plugs ejected under pressure, or sudden kickback from the release of stored elastic energy during plug installation, can cause serious bodily injury.

To learn more: **(800) 456-8721 • info@USAIndustries.com • USAIndustries.com**

M-TP-SURESNA^{PRO}-V.1.0.4

S. Houston, TX | Corpus Christi, TX | Prairieville, LA | Broken Arrow, OK

©2025 USA Industries • ISO 9001:2015

